

# PTFE TAPE

Series

Product Specifications

# TITASEAL®



## Specifications

Rated working pressure of 2000Kpa

Temperature range - 10°C to +200°C

## Sizing Chart MM

	SIZE	COLOUR
M103	12MM X 0.1 X 10MTR	PINK
M104	12MM X 0.1 X 30MTR	PINK
M105	12MM X 0.1 X 10MTR	YELLOW
M106	12MM X 0.1 X 30MTR	YELLOW
M108	12MM X 0.1 X 10MTR	GREY
M109	12MM X 0.1 X 30MTR	GREY

## Application

PTFE tape can be used on pipe made from galvanised steel, iron, brass, copper, aluminum, stainless steel, polyethylene, polypropylene, PVC, CPVC, ABS or fibreglass.

It can also be used on pipes carrying the following materials: Diesel fuel oil, gasoline, alcohols, heating oils, hydraulic fluids, steam, water etc.

Store in a cool, dry conditions between 5°C and 25°C. Do not use on pipes, which contain liquid oxygen or flourine.

## Features

AGA Approved Class III

Conforms to AS 1272-1974

Will not harden or crack on the joint.

Acts as a thread lubricant and anti-seize

Prevents electrolytic corrosion of threads

Non-toxic

Non-flammable

Unlimited shelf life

Available in Grey, Yellow and Pink

Suitable for potable water

Non flammable

## Description

PTFE (Polytetrafluoroethylene) tape is a non-adhesive tape for use with threaded fittings on all types of pipes, including gas and liquid carrying pipework, including potable water.



AGA 6970 G

For more information on Titaseal, contact:

Austworld 15 Activity Crescent, Molendinar, Queensland 4214 Australia

P. 1300 780 430

F. 1300 780 441

E. [info@austworld.com.au](mailto:info@austworld.com.au)

Austworld Pty Ltd. All rights reserved 2018. Austworld and Titaseal are registered trade mark belonging to Austworld Pty Ltd.

**AW**  
AUSTWORLD